

AMENDMENT AND PRESENTATION OF CLAIMS

Please replace all prior claims in the present application with the following claims, in which claims 13, 14, 24 through 28, 35, and 36 are amended.

1-12. (Canceled)

13. (Currently Amended) A method, comprising:

determining, by an apparatus, cluster centers in a first data structure, wherein the first data structure comprises a lattice structure of weight vectors that create an approximate representation of a plurality of input data points; and wherein a plurality of the weight vectors represents a single non-linear cluster;

performing, by the apparatus, a first iterative process ~~for iteratively~~ with iterations each including determining a winner weight vector for each data point and then updating each of the weight vectors with a corresponding first coefficient updated in a second iterative process such that the weight vectors move toward the cluster centers;

performing ~~[[a]],~~ by the apparatus, the second iterative process ~~for iteratively~~ with iterations each including updating said corresponding first coefficient in a second data structure by utilizing the winner weight vector determined in the first iterative process ~~results of the iterative updating of the first data structure;~~ and

determining by the apparatus, based on the second data structure, several sets of weight vectors in said lattice structure such that in each set, the weight vectors correspond to the same cluster centers of the input data points,

wherein the method is an unsupervised method that is configured to be suitable for an on-line system.

14. (Currently Amended) The method according to claim 13,

wherein ~~each iteration in the first iterative process comprises selecting a~~ the winner weight vector for each data point is determined on the basis of the distance between the data point and the weight vectors, and

each iteration in the first iterative process further includes calculating a next value for each weight vector on the basis of the current value of the weight vector and a first neighborhood function of the distance on the lattice structure between the weight vector and the winner weight vector, and

wherein ~~the second data structure comprises a first coefficient for each of the weight vectors in the lattice structure and~~ each iteration in the second iterative process further includes ~~comprises~~ calculating a next value of each of the first coefficients based on:

the current value of the each first coefficient, and

a combination of

a first coefficient of the winner weight vector,

a second neighborhood function of the distance on the lattice structure between the weight vector and the winner weight vector, and

an adjustment factor for adjusting convergence speed between iterations.

15. (Previously Presented) The method according to claim 13, wherein the determining the weight vectors that correspond to cluster centers comprises selecting local maxima in the second data structure.

16. (Previously Presented) The method according to claim 14, wherein the combination is or comprises multiplication.

17. (Previously Presented) The method according claim 14, wherein the second neighborhood function is not monotonous.

18. (Previously Presented) The method according to claim 14, wherein the first coefficients are limited to a range [0,1] and the second neighborhood function gives negative or positive values, respectively, for some distances.

19. (Previously Presented) The method according to claim 14, wherein the second neighborhood function depends on a number of prior iterations.

20. (Previously Presented) The method according to claim 13, wherein the input data points represent real-world quantities.

21. (Previously Presented) The method according to claim 14, wherein the first data structure is or comprises a self-organizing map.

22. (Previously Presented) The method according to claim 21, further comprising:

estimating an upper limit K for a number of clusters in the self-organizing map;

defining a coefficient vector $\Theta_i = (\theta_{i,1}, \theta_{i,2}, \dots, \theta_{i,K})$ for each weight vector i in the self-organizing map, the coefficient vector comprising K second coefficients $\theta_{i,l}$, each of which represents a weighting between the weight vector i and a label l ; and

assigning cluster label l to weight vector i if:

$$l = \arg \max \theta_{i,k},$$

$$1 \leq k \leq K$$

23. (Previously Presented) The method according to claim 22, wherein each iteration in the second iterative process comprises calculating a next value of each second coefficient based on the current value of the second coefficient and a combination of

a coefficient of the winner weight vector,

a third neighborhood function of distance, and

an adjustment factor for adjusting convergence speed between iterations.

24. (Currently Amended) A computer-readable program product comprising a computer program code embodied on a computer-readable medium, the computer-readable program ~~product being configured to control~~ code which, when executed by a processor to perform, causes an apparatus to perform at least the following:

determining cluster centers in a first data structure, wherein the first data structure comprises a lattice structure of weight vectors that create an approximate representation of a plurality of input data points; and wherein a plurality of the weight vectors represents a single non-linear cluster;

performing a first iterative process ~~for iteratively~~ with iterations each including determining a winner weight vector for each data point and then updating each of the weight vectors with a corresponding first coefficient updated in a second iterative process such that the weight vectors move toward the cluster centers;

performing ~~[[a]]~~ the second iterative process for iteratively with iterations each including updating said corresponding first coefficient in a second data structure by utilizing the winner weight vector determined in the first iterative process ~~results of the iterative updating of the first data structure;~~ and

determining, based on the second data structure, several sets of weight vectors in said lattice structure such that in each set, the weight vectors correspond to the same cluster centers of the input data points,

wherein the executing the computer program is configured to carry out an unsupervised method that is configured to be suitable for an on-line system.

25. (Currently Amended) An apparatus, comprising:

first determination means for determining cluster centers in a first data structure, wherein the first data structure comprises a lattice structure of weight vectors that create an approximate representation of a plurality of input data points; and wherein a plurality of the weight vectors represents a single non-linear cluster;

first performance means for performing a first iterative process ~~for iteratively~~ with iterations each including determining a winner weight vector for each data point and then updating each of the weight vectors with a corresponding first coefficient updated in a second iterative process such that the weight vectors move toward the cluster centers;

second performance means for performing ~~[[a]]~~ the second iterative process ~~for iteratively with iterations each including updating said corresponding first coefficient in a second data structure by utilizing the winner weight vector determined in the first iterative process results of the iterative updating of the first data structure;~~ and

second determination means for determining, based on the second data structure, several sets of weight vectors in said lattice structure such that in each set, the weight vectors correspond to the same cluster centers of the input data points,

wherein the apparatus is configured to operate using an unsupervised method that is configured to be suitable for an on-line system.

26. (Currently Amended) An apparatus, comprising:

[[a]] at least one processor ~~configured to;~~ and

at least one memory including computer program code,

wherein the at least one memory and the computer program code configured to, with the

at least one processor, cause the apparatus to perform at least the following:

determine cluster centers in a first data structure, wherein the first data structure comprises a lattice structure of weight vectors that create an approximate representation of a plurality of input data points; and wherein a plurality of the weight vectors represents a single non-linear cluster;

perform a first iterative process ~~to iteratively update~~ with iterations each including determining a winner weight vector for each data point and then updating each of the weight vectors with a corresponding first coefficient updated in a second iterative process such that the weight vectors move toward the cluster centers;

perform [[a]] the second iterative process ~~to iteratively update~~ with iterations each including updating said corresponding first coefficient in a second data structure by utilizing the winner weight vector determined in the first iterative process ~~results of the iterative updating of the first data structure;~~ and

determine, based on the second data structure, several sets of weight vectors in said lattice structure such that in each set, the weight vectors correspond to the same cluster centers of the input data points,

wherein the apparatus is configured to operate using an unsupervised method that is configured to be suitable for an on-line system.

27. (Currently Amended) The apparatus of claim 26, wherein the apparatus is further caused
~~processor is further configured to:~~

~~select a~~ determine the winner weight vector for each data point on the basis of the distance
 between the data point and the weight vectors; [[and]]

calculate a next value for each weight vector on the basis of the current value of the weight
 vector and a first neighborhood function of the distance on the lattice structure between
 the weight vector and the winner weight vector[[,]]; and

~~wherein the second data structure comprises a first coefficient for each of the weight vectors
 in the lattice structure and each iteration in the second iterative process comprises
 ealeulating~~ calculate a next value of each of the first coefficients based on:

the current value of the each first coefficient, and

a combination of

a first coefficient of the winner weight vector,

a second neighborhood function of the distance on the lattice structure between the
 weight vector and the winner weight vector, and

an adjustment factor for adjusting convergence speed between iterations.

28. (Currently Amended) The apparatus of claim 27, wherein the ~~processor~~ apparatus is
 further ~~configured~~ caused to determine the weight vectors that correspond to cluster centers by
 selecting local maxima in the second data structure.

29. (Previously Presented) The apparatus of claim 27, wherein the combination is or comprises
 multiplication.

30. (Previously Presented) The apparatus of claim 27, wherein the second neighborhood function is not monotonous.

31. (Previously Presented) The apparatus of claim 27, wherein the first coefficients are limited to a range [0,1] and the second neighborhood function is configured to give negative or positive values, respectively, for some distances.

32. (Previously Presented) The apparatus of claim 27, wherein the second neighborhood function depends on a number of prior iterations.

33. (Previously Presented) The apparatus of claim 27, wherein the input data points represent real-world quantities.

34. (Previously Presented) The apparatus of claim 27, wherein the first data structure is or comprises a self-organizing map.

35. (Currently Amended) The apparatus of claim 27, wherein the apparatus is further caused ~~processor is further configured~~ to:

estimate an upper limit K for a number of clusters in the self-organizing map;

define a coefficient vector $\Theta_i = (\theta_{i,1}, \theta_{i,2}, \dots, \theta_{i,K})$ for each weight vector i in the self-organizing map, the coefficient vector comprising K second coefficients $\theta_{i,l}$, each of which represents a weighting between the weight vector i and a label l ; and

assign cluster label l to weight vector i if:

$$l = \arg \max \theta_{i,k},$$

$$1 \leq k \leq K$$

36. (Currently Amended) The apparatus of claim 27, wherein the wherein the apparatus is further caused ~~processor is further configured~~ in each iteration in the second iterative process to calculate a next value of each second coefficient based on the current value of the second coefficient and a combination of

a coefficient of the winner weight vector,

a third neighborhood function of distance, and

an adjustment factor for adjusting convergence speed between iterations.